

ANTI-GRAFFITI COATING

PRODUCT DESCRIPTION

- Anti-Graffiti Coating will protect against spray paint, fly poster, contamination and weathering with ease, (no harsh chemicals or removers needed), contaminants can simply be wiped-away with water.
- New ground breaking technology enables extremely low dirt pickup on treated surfaces.
- Ideal for: concrete & facades, most metal including signs & cladding, painted surfaces such as utility boxes & render, masonry such as brick and stone, interior / exterior marble & granite.

APPLICATION

Always carry out a test area first to ensure the finished result is acceptable.

- Do not apply during rain, frost or in direct sun, apply only when temperature between 5°- 25 °C.
- Ensure surface is clean, dry and dust free. Remove any stains or efflorescence. Any previous coatings must be fully cured before application.
- Apply using a brush or short pile/gloss roller or airless sprayer ensuring an even coat. Avoid runs, drips and foaming - do not use a foam roller.
- For more porous surfaces, apply a second coat immediately (maximum 30 minutes, once the first coat is dry).
- Clean tools and equipment immediately after use with white spirit.

RECOMMENDATIONS

- Wear protective gloves and appropriate clothing whilst using the product.

COVERAGE:

1 Litre will cover approx. 5 - 10m²

(depending on porosity and texture of the surface)

PRECAUTIONS FOR USE

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS)

Important: The content of this documentation is based on our experience of the product. PROTECTiT SP guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application, application by unqualified personnel, use of products not compatible with PROTECTiT SP products or bad weather conditions.

KEY FEATURES

- Up to 30 cleaning cycles protection
- Prevents ingress of all types of graffiti (spray paint & marker)
- Suitable for natural stone, brick, porous wall & roof building substrates
- Dry in 30 minutes



TECHNICAL DATA

- **Colour:** Clear
- **Odour:** Slightly Solvent
- **Form:** Ready to Use - Liquid
- **Drying time:** 30min, re-coat: 4 hours dependant on weather conditions
- **Application Temperatures:**
Minimum +5°C
Maximum 25°C

Shelf Life & Storage: 24 months from the date of manufacture in the original unopened container. Store locked up in dry place between 5°C and 30°C in the original container.