

# COLOUR ENHANCER

## PRODUCT DESCRIPTION

- Colour Enhancer is an aqueous fluoropolymer dispersion which enhances the colour of natural stone and porous building substrates.
- Colour Enhancer is UV resistant and does not discolour over time.
- Colour Enhancer can be applied to vertical, horizontal, indoor and outdoor surfaces such as natural stone, brick, terracotta, limestone, slate or cement surfaces.

## IMPORTANT BEFORE USE

Colour enhancement will vary according to the surface. Do not use on crystallized, polished materials or ceramics. Do not apply during rain, frost or in direct sun. Apply only when temperature is between 5°- 30°C. Always use product in a ventilated space.

Use PROTECTiT Efflorescence Remover if any efflorescence is visible prior to application. Domestic stains can be cleaned with PROTECTiT Oil Remover. Following traffic induced wear colour enhancement can be regenerated by re-applying product. For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).

## APPLICATION

Always test a small area before proceeding to ensure finished result is acceptable.

- Ensure surface is clean, dry and dust free, remove any stains before application. Shake container well before use, do not dilute and do not mix with another product.
- The treated surface should be impregnated to saturation point, either in one, two or three applications 'wet-on-wet' to give desired finish.
- Apply using a brush or roller ensuring an even coat. Avoid any runs, drips or puddling by removing excess product from the surface during application. Do not allow the product to dry between coats.
- Allow up to 4 hours drying time. Allow the product to cure overnight before subjecting to heavy traffic. Clean equipment with soapy water after use.

## COVERAGE

1 Litre covers 4 - 6m<sup>2</sup> (depending on porosity and texture of the surface)

**Important:** The content of this documentation is based on our experience of the product. PROTECTiT SP guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application, application by unqualified personnel, use of products not compatible with PROTECTiT SP products or bad weather conditions.

## KEY FEATURES

- Enriches & stabilises the natural colour of stone, brick, limestone, terracotta, slate & cement surfaces
- Transparent protective seal against dirt, water, oil, grease, moss & algae
- Hardwearing & long lasting finish
- For indoor & outdoor use



## TECHNICAL DATA

- **Colour:** Milky
- **Chemical Composition:** Aqueous fluoropolymer dispersion
- **Density:** 1.0kg/lit @ 25°C
- **Flashpoint:** > 55°C
- **Chemical Resistance:** Dilute acids and alkalis, water and de-icing salts.

**Shelf Life & Storage:** 24 months from the date of manufacture in the original unopened container. Store locked up in dry place between 5°C and 25°C in the original container.