

# GROUT FILM REMOVER

### **PRODUCT DESCRIPTION**

- Ideal for removing grout and mortar residues leftover from tiling and grouting.
- Mild acids and surfactants dissolve and emulsify difficult to remove residues.
- Ideal for use on glazed and unglazed ceramics and any acid resistant stone.

#### **APPLICATION**

Always test a small area before proceeding to ensure finished result is acceptable.

- Apply a saturated coat to the area and leave to activate/ dissolve the grout for up to 5 minutes.
- Agitate the surface with a brush or scotch pad.
- Rinse away residue with clean warm water. If the area still appears to be contaminated, repeat the process until no residues remain. Do not let the product dry on the surface.
- Remove as much excess product as possible and clean tools and equipment immediately after use with soapy water.

# **RECOMMENDATIONS**

- Wear protective gloves and appropriate clothing whilst using the product
- DO NOT USE ON MARBLE OR ACID SENSITIVE SUBSTRATES.
- Keep out of reach of children.
- Keep in a dry place between 5°C and 30°C in the original container.

# PRECAUTIONS FOR USE

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS)

# **KEY FEATURES**

- Removes grout and mortar residues
- Easy to use
- Interior and exterior use
- Covers upto 15m<sup>2</sup>
- Non fuming



# PRODUCT CHARACTERISTICS

Colour: Pale pink

Odour: Barely perceptible

Form: Liquid

• **PH:** approx. 2

Specific Gravity @ 25°C: 1.01

Application Temperatures:

- Minimum +5°C

- Maximum 30°C

 Shelf life: 24 months from the date of manufacture in the original unopened container.

**Important:** The content of this documentation is based on our experience of the product. PROTECTIT SP guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application, application by unqualified personnel, use of products not compatible with PROTECTIT SP products or bad weather conditions.