

LIMESCALE REMOVER

PRODUCT DESCRIPTION

- Ideal for removing limescale buildup, grout and mortar residues that are often stubborn and difficult to remove.
- The surface will be left easy to clean and free from stubborn stains. Ideal for use on glazed and unglazed ceramics can be used on toilets, sinks, showers, floors and any acid resistant surface.

APPLICATION

Always test a small area before proceeding to ensure finished result is acceptable.

DO NOT use on marble or acid sensitive substrates. Product is ready to use and should not be diluted.

- Shake container before use. Apply a saturated coat to the area, leave to activate for up to 5 minutes depending on the level of contamination.
- Agitate the surface with a brush or scotch pad.
- If the area still appears to be contaminated, repeat the process until no
 residues remain. Do not leave the product on the surface for long periods of
 time and do not allow the product to dry out.

RECOMMENDATIONS

- Do not allow to come in to contact with clothing, fabrics, metals or carpets as bleaching will occur.
- Wear protective gloves whilst using the product.
- Keep out of reach of children.
- Keep in a dry place between 5°C and 30°C in the original container.

PRECAUTIONS FOR USE

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS)

KEY FEATURES

- Fast acting and easy to use
- Removes limescale build-up, grout and mortar residues
- Ideal for sinks, showers, toilets and floors
- Interior and exterior use



PRODUCT CHARACTERISTICS

Colour: Colourless

• Odour: Apple

Specific Gravity @ 25°C: 1.00

• **PH:** approx. 2

 Shelf life: 24 months from the date of manufacture in the original unopened container.

 Storage: Keep out of reach of children. Keep in a dry place between 5°c and 30°c in the original container.

Important: The content of this documentation is based on our experience of the product. PROTECTIT SP guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application, application by unqualified personnel, use of products not compatible with PROTECTIT SP products or bad weather conditions.