

OIL OFF

PRODUCT DESCRIPTION

- Super concentrated formula that removes oil from most porous substrates with no residue or contamination left behind.
- Oil Off penetrates deep into the pores of the surface, lifting the oil away on a microscopic level.

IMPORTANT BEFORE USE

Do not mix with acids or other cleaning products. Do not allow product to come into contact with plants, shrubs or grass. Do not apply during rain, frost or when surface and air temp is <5°C & >30°C. Never proceed without carrying out a test patch to ensure surface compatibility. For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).

APPLICATION

Always test a small area before proceeding to ensure finished result is acceptable.

- Apply a saturated coat to the affected area.
- Allow to work for up to 1 hour depending on the level of staining.
- Remove from the surface using hot water or a jet wash.
- Do not apply during rain, frost or very hot weather.
- Clean all tools and equipment with soapy water after use.

SHELF LIFE & STORAGE

24 months from the date of manufacture in the original unopened container.

Store locked up in dry place between 5°C and 30°C in the original container.

KEY FEATURES

- Concentrated formula
- The ultimate oil and grease remover
- Suitable for driveways, patios, wood, decking, warehouse, garage and industrial use



TECHNICAL DATA

- **Form:** Liquid
- **Appearance:** Pale Yellow
- **Odour:** Mild characteristic odour
- **pH:** 13+/- 0.5
- **Density:** 1.06
- **Solubility in water:** Fully soluble
- **VOC:** < 100g/litre
- **Coverage:** upto 5m²/Ltr

Important: The content of this documentation is based on our experience of the product. PROTECTiT SP guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application, application by unqualified personnel, use of products not compatible with PROTECTiT SP products or bad weather conditions.