

# PAINT & VARNISH STRIPPER

## PRODUCT DESCRIPTION

- Fast acting paint, varnish and lacquer stripper for use on wood, metal and masonry.
- The new non-drip formula is ideal for vertical and horizontal applications.
- Water washable for easier clean up.

## IMPORTANT BEFORE USE

Always test a small hidden portion of the substrate before use, to ensure the final result is satisfactory and to calculate consumption. Ensure the surface(s) to be stripped are dry before applying the product.

Protection should be provided for floor coatings that you do not wish to remove or any surface that may be damaged by the product e.g. perspex, plastics, rubber etc.

Do not apply during rain or frost and when surface air temperature is <5°C and > 30°C. Do not apply in direct sunlight.

## APPLICATION

Always test a small area before proceeding to ensure finished result is acceptable.

- Read separate MSDS before use. Shake container well to ensure uniform consistency. Cover the top of the container with a cloth during opening to avoid splashes.
- Apply a thick even coat by brush - DO NOT BRUSH OUT. The thicker/more layers of paint, the more product you will require and the longer you will need to leave the product to work.
- Leave for approx. 60 minutes until the paint or varnish reacts (for some coatings begins to blister). For multi layered surfaces (5 or more), apply a second generous coat.
- After the product has penetrated into the substrate, remove softened coating/paint with a scraper. For a professional finish rub down with stainless steel scourer, never use steel wool. On wood, follow the grain. Rinse with clean cold water and allow to dry.
- Remove as much excess product as possible and clean tools and equipment immediately after use with soapy water.

## KEY FEATURES

- Powerful & effective stripper
- Suitable for a variety of surfaces - walls, wood, concrete, vehicles
- Lower evaporation, fewer fumes
- Fast blistering & results
- Easy & safe to use
- Water washable for easier clean up



## SHELF LIFE & STORAGE

24 months from the date of manufacture in the original unopened container. Store locked up in dry place between 5°C and 25°C in the original container.

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).

**Important:** The content of this documentation is based on our experience of the product. PROTECTiT SP guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application, application by unqualified personnel, use of products not compatible with PROTECTiT SP products or bad weather conditions.