

# PAVING & PATIO SEALER

## PRODUCT DESCRIPTION

- Paving & Patio Sealer is an impregnating sealer which protects all porous materials such as concrete paving, brick, granite, marble, polished concrete, sandstone.
- May be used on internal and external surfaces on new or renovated works.
- Stains cannot penetrate a treated surface making them easier to clean and chewing gum easier to remove.
- A treated surface will remain moisture and vapour permeable.
- Easy to apply to all surfaces, you can use the surface within 1 hour of application.
- Helps reduce further on-going maintenance and costs on a protected surface.
- Prevents surfaces from deteriorating through repeated "Freeze/Thaw" cycles.

## IMPORTANT BEFORE USE

Product is ready to use and should not be diluted. Ensure surface is dry before application. Do not pour directly on to surface. Do not apply if rain is expected within 4 hours. Do not apply during rain or frost and when surface air temperature is <5°C and >30°C. Once a fully treated surface is dry the product cannot be reapplied as there will be a loss of adhesion. Keep pets/children away until surface is completely dry.

## APPLICATION

Always carry out a test area first to ensure the finished result is acceptable.

- Shake container before use. Remove surface contamination. Surface should be clean, free from dust, dirt, oil, efflorescence, organic growth, coatings and sealers. All algae and mould should be treated and removed using Algae Remover before application.
- Ideally apply using a garden sprayer, alternatively you can use a brush or roller.
- The surface should be impregnated to saturation point, recommended one to three applications 'wet-on-wet'. DO NOT allow the product to dry in between applications. Avoid runs, drips or pooling by removing excess product from the surface.
- Remove as much excess product from your tools as possible and clean equipment with soapy water.
- Water and stain resistance is evident after initial curing but may take up to 7 days to reach 100% efficiency.

## COVERAGE:

1 Litre will cover approx. 6 - 8m<sup>2</sup> (depending on porosity and texture of the surface)

**Important:** The content of this documentation is based on our experience of the product. PROTECTiT SP guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application, application by unqualified personnel, use of products not compatible with PROTECTiT SP products or bad weather conditions.

## KEY FEATURES

- The Market Leading, proven long lasting impregnating sealer
- Many prestigious Public realm jobs completed
- Will last up to 10 years
- Repels oil, dirt & moisture
- For paving, patios, driveways & more



## TECHNICAL DATA

- **Chemical Composition:** Aqueous fluoropolymer dispersion.
- **Density:** 1.0kg / lt @ 25°C
- **Chemical Resistance:** Mild acids and alkalis, water and de-icing salts.
- **Coverage:** Dependant on porosity
- **VOC Content:** 0.0g / litre

**Shelf Life & Storage:** 24 months from the date of manufacture in the original unopened container. Store locked up in dry place between 5°C and 30°C in the original container.

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS)